Industry press has credited photoluminescent (PL) pathway markings, installed in the World Trade Center after the initial 1993 terrorist attack, with significantly improving evacuation time during the tragic events of 9/11. Since that time, revolutionary PL Low Location Exit Path Marking Systems (LLEPM) using our products have been successfully installed in the Pentagon and other Federal government buildings and in commercial buildings as well.

Although acclaimed as highly effective, current standard top-quality PL safety materials are not always suitable for every building application, particularly in older buildings where contact surfaces are irregular or highlyworn. That's why AfterGlow LLC has developed a state-of-the art series of premium PL paint solutions. Our family of AfterGlo® Brand photoluminescent (PL) paints addresses these special situations and other challenges.

# Advantages of our AfterGlo<sup>®</sup> PL paint systems:

- No external power source required the ultimate "green solution"
- Activated by existing ambient lighting
- Fully charges and recharges in minutes
- Can be recharged over and over
- Nonradioactive and nonhazardous
- Extremely bright visible to dark-adapted eyes
- Extremely durable
- Maintenance-free, saving you money and time
- 100% reliable

Use our AfterGlo<sup>®</sup> Brand PL paints in place of or in addition to other PL safety materials in stairwells, corridors, group offices and public areas, common areas, and spaces where emergency equipment is stored.

### Who is AfterGlow, LLC?

AfterGlow LLC is a dynamic small business dedicated to providing its customers with the finest and most appropriate photoluminescent safety materials. The AfterGlow LLC staff enjoys a reputation earned over many years for technical, managerial and manufacturing excellence. We support our customers with the very best, most appropriate, and most costeffective photoluminescent safety solutions for our customers' particular needs.

Customer questions or concerns can be addressed to:

#### Herb Jones

Program Manager AfterGlow LLC 181 Industrial Park Drive Trenton, NC 28585-0091 Tel: (252) 448-1019 ext. 3204 E-mail: hjones@afterglowllc.com

Visit us on the web at **www.afterglowllc.com** or visit our web store at **www.afterglowdirect.com** 



## AfterGlo<sup>®</sup> Photoluminescent Safety Paint



### AfterGlo<sup>®</sup> High Performance Green DHI Part Number: HPP012DGNK-P

- Assigned MEA number 387-07-M; certified for use in New York City under Local Law 26.
- Cost-effective industrial-quality high performance PL paint developed in 2007.
- One-coat PL application over white base coat.
- No protective top-coat required, but is recommended for increased durability.
- Pale-green daytime color, extremely bright green afterglow (requires easy pigment mixing just prior to application).
- Pigment never loses its brightness.
- Can be brushed or rolled directly on concrete, wood, metal or painted surfaces.
- Can be sprayed with proper equipment.
- Can be used on floors as well as vertical surfaces such as door trim.
- Tough abrasion-resistant acrylic polymer resists wear.
- Easy soap and water cleanup of brushes and spills while paint is still wet.
- Once cured, can be washed with household cleaners and a stiff bristle brush.
- Substantially exceeds MEA requirements.



Available in Sizes 20z, 40z, 80z, 160z, 320z, and 1220z

### AfterGlo<sup>®</sup> High Performance Green DHI Part Number: HPPBP01-IBCK-P

- Complies with IBC 2009 Section 1024.4
- Cost-effective industrial-quality high performance PL paint developed in 2011.
- Two-coat PL application over white base coat.
- No protective top-coat required, but is recommended for increased durability.
- Green daytime color, extremely bright green afterglow (requires easy pigment mixing just prior to application).
- Pigment never loses its brightness.
- Can be brushed or rolled directly on concrete, wood, metal or painted surfaces.
- Can be sprayed with proper equipment.
- Can be used on floors as well as vertical surfaces such as door trim.
- Tough abrasion-resistant acrylic polymer resists wear.
- Easy soap and water cleanup of brushes and spills while paint is still wet.
- Once cured, can be washed with household cleaners and a stiff bristle brush.
- Substantially exceeds IBC requirements.

